



SPECIFICATIONS

MODEL/WATER CAPACITY (LBS.)	1,000 POUND
HEIGHT (IN.)	57.3
HEIGHT (MM)	1,455
WATER CAPACITY (KG)	450
NOMINAL TARE WEIGHT (LBS.)	334
NOMINAL TARE WEIGHT (KG)	151.5
CYLINDER DIAMETER (IN.)	30
CYLINDER DIAMETER (MM)	762
CYLINDER VOLUME (CU. IN.)	27,461
CYLINDER VOLUME (LITERS)	450
COLLAR DIAMETER (IN.)	16
COLLAR DIAMETER (MM)	406.4
COLLAR HEIGHT (IN.)	6.9
COLLAR HEIGHT (MM)	175
FOOTRING DIAMETER (IN.)	22
FOOTRING DIAMETER (MM)	558.8
STANDARD SPECIFICATION	DOT-4BW-260
SERVICE PRESSURE (PSIG)	260
SERVICE PRESSURE (BAR)	17.9
TEST PRESSURE (PSIG)	520
TEST PRESSURE (BAR)	35.9
OPTIONAL SPECIFICATION	DOT-4BW-400
SERVICE PRESSURE (PSIG)	400
SERVICE PRESSURE (BAR)	27.6
TEST PRESSURE (PSIG)	800
TEST PRESSURE (BAR)	55.2